MOYTRONIX

Visitor Check-In Kiosk

Self-service visitor sign-in with ID badge printing — part of the QFusion platform

First impressions start at reception. The Visitor Check-In Kiosk lets guests sign themselves in — scan a QR from their pre-registration email or tap NFC, sign NDAs, GDPR and health & safety notices on screen, and walk away with a printed, encoded ID badge in seconds while the host gets an instant notification. Built on a modular commercial kiosk: camera, scanner and thermal printer behind a lockable, tool-free front door, wall-mounted, desktop or on the optional floor stand.



Reception installation



Printed & encoded ID badge

■ Badge printing & encoding

Prints and encodes visitor ID badges in seconds from the integrated thermal printer.

■ QR / NFC contactless

Scanner with LED assist reads pre-registration QR codes; NFC tap supported.

■ Pre-registration & host alerts

Guests register before arrival; hosts are notified the moment their visitor checks in.

■ Compliance on screen

NDA, GDPR and health & safety sign-off captured digitally at check-in.

■ Modular hardware

POS host, camera, printer and scanner combine freely; tool-free service via lockable front door.

■ Flexible mounting

Anti-theft flush wall mount, desktop, or optional floor stand.

Model	21.5" Check-In Kiosk	23.8" Check-In Kiosk
Panel	21.5" IPS, FHD 1920×1080, 300 cd/m²	23.8" IPS, FHD 1920×1080, 300 cd/m²
Touch	PCAP, recessed wipe-clean glass	PCAP, recessed wipe-clean glass
Glass	Thermally toughened, 6H anti-scratch, anti-reflective	Thermally toughened, 6H anti-scratch, anti-reflective
Android built in	Android 11 · RK3568 quad 2.0 GHz · 2 GB / 32 GB	Android 11 · RK3568 quad 2.0 GHz · 2 GB / 32 GB
Peripherals	Thermal printer · QR/barcode scanner · optional camera & POS bracket	Thermal printer · QR/barcode scanner · optional camera & POS bracket
Connectivity	Wi-Fi + Ethernet · USB ×2 · opt. 4G	Wi-Fi + Ethernet · USB ×2 · opt. 4G
Power	28 W max · built-in PSU	33 W max · built-in PSU
Mounting	Wall (anti-theft flush) / desktop / floor stand	Wall (anti-theft flush) / desktop / floor stand
Operation	24/7 · 0°C to 45°C indoor	24/7 · 0°C to 45°C indoor

In development as part of the QFusion platform — early enquiries welcome; final specification may vary.